



FABRICATED FROM 6063-T52 EXTRUDED ALUMINUM						
MODEL	L	O.D.	I.D.	X	Y	TYWRAP●
FOS-10	23.125"	11.36"	10.125"	0.617"	0.650"	N
FOS-1	26.125"	13.36"	12.125"	0.617"	0.650"	Y
* FOS-2	26.125"	13.36"	12.125"	0.617"	1.250"	Y
FOS-3	31.50"	17.69"	16.125"	0.780"	0.900"	Y
* FOS-3D	31.50"	17.69"	16.125"	0.755"	1.500"	Y
FOS-4	32.625"	19.69"	18.125"	0.780"	0.900"	Y
* FOS-5	32.625"	19.83"	18.125"	0.850"	1.750"	Y
FOS-20	33.750"	21.36"	20.125"	0.617"	1.250"	Y
FOS-24	37.750"	25.36"	24.125"	0.617"	1.250"	Y
FOS-30	44.250"	31.36"	30.125"	0.617"	1.250"	Y

TYWRAP● INDICATES TYWRAP EYELET IN CENTER OF LARGE RADIUS.

MODEL	L	O.D.	I.D.	X	Y
FOSP-12-TMK	17.63"	13.10"	12.00"	0.550"	0.75"
FOSP-17-TMK	25.25"	18.94"	17.50"	0.815"	0.95"

The chart above is for reference only. Please contact your cable manufacturer for exact minimum bend radii.